

Blue Globe-S2

Material: Edelstahl (1.4305)
Dichteinsatz: TPE blau
O-Ring: NBR
Einsatztemperatur: -40 °C bis 130 °C
Schutzart: IP 68 bis 15bar/IP 69K

Material: stainless steel (AISI 303)
Sealing insert: TPE blue
O-ring: NBR
Temperature range: -40 °C to 130 °C
Protection type: IP 68 up to 15bar/IP 69K

103.30
103.50

Weitere internationale Zulassungen vorhanden

Further international approvals available




Gewinde Entry Thread AG	\varnothing mm	\varnothing mit Inlet / with inlet mm	H mm	GL mm	HUGRO No.	
M 12 x 1,5	2 - 8	2 - 5	17	21	5	103.150808.30
M 16 x 1,5	4 - 11	4 - 7	20	25	6	103.171111.30
M 20 x 1,5	5 - 14	5 - 9	24	29	6,5	103.201414.30
M 25 x 1,5	11 - 20	11 - 16	30	30	7,5	103.252020.30
M 32 x 1,5	15 - 25	15 - 20	36	32	8	103.322525.30
M 40 x 1,5	20 - 32	20 - 26	45	35	8	103.403232.30
M 50 x 1,5	31 - 42	31 - 35	57	39	10	103.504242.30
M 63 x 1,5	41 - 54	41 - 46	68	40	10	103.635454.30
M 75 x 1,5	54 - 65	54 - 58	81	47	15	103.746565.30
M 85 x 2	65 - 77	65 - 70	95	49	15	103.8F7777.30

langes Anschlussgewinde / long entry thread

M 12 x 1,5	2 - 8	2 - 5	17	21	15	103.150808.50
M 16 x 1,5	4 - 11	4 - 7	20	25	15	103.171111.50
M 20 x 1,5	5 - 14	5 - 9	24	29	15	103.201414.50
M 25 x 1,5	11 - 20	11 - 16	30	30	15	103.252020.50
M 32 x 1,5	15 - 25	15 - 20	36	32	15	103.322525.50
M 40 x 1,5	20 - 32	20 - 26	45	35	15	103.403232.50
M 50 x 1,5	31 - 42	31 - 35	57	39	15	103.504242.50
M 63 x 1,5	41 - 54	41 - 46	68	40	15	103.635454.50

Auf Anfrage:
- in Edelstahl 1.4571

On request:
- in stainless steel 1.4571



Hygienic

Cable Glands

EMC Protection

Ex Protection

Conduit Protection Syst.

Accessories

Technical Appendix

Article Number Index