

Ex Compact

Material: Messing vernickelt
 Dichteinsatz: HNBR
 O-Ring: FPM
 Einsatztemperatur: -60 °C bis 105 °C
 Schutzart: IP 68 (30 bar)/IP 69K

Material: Nickel-plated brass
 Sealing insert: HNBR
 O-ring: FPM
 Temperature range: -60 °C to 105 °C
 Protection type: IP 68 (30 bar)/IP 69K



118.00


Zertifikate: PTB 10 ATEX 1034 X
 IECEx PTB 12.0055 X

Certificates: PTB 10 ATEX 1034
 IECEx PTB 12.0055 X



Ex II 2G Ex d IIC + Ex e II
 II 2 D Ex tD A21 IP68

Gewinde Entry Thread AG	 mm	 mm	H mm	GL mm	Ex Compact MS	HUGRO No.
M 16 x 1,5	3 - 7	21	25	12	EX1126.17.070	118.1707.00
M 16 x 1,5	5 - 10	24	25	12	EX1126.17.100	118.1710.00
M 20 x 1,5	5 - 11	24	25	12	EX1126.20.110	118.2011.00
M 20 x 1,5	9 - 14	30	25	12	EX1126.20.140	118.2014.00
M 25 x 1,5	7,5 - 15	32	26,5	12	EX1126.25.150	118.2515.00
M 25 x 1,5	12,5 - 18	32	26,5	12	EX1126.25.180	118.2518.00
M 32 x 1,5	17 - 23	41	32	12	EX1126.32.230	118.3223.00
M 32 x 1,5	21 - 26	41	32	12	EX1126.32.260	118.3226.00
M 40 x 1,5	21 - 26	41	32	14	EX1126.40.260	118.4026.00
M 40 x 1,5	24 - 32	50	33	14	EX1126.40.320	118.4032.00
M 50 x 1,5	28 - 36	55	33	14	EX1126.50.360	118.5036.00
M 50 x 1,5	35 - 42	60	34	14	EX1126.50.420	118.5042.00
M 63 x 1,5	36 - 44	65	35	14	EX1126.63.440	118.6344.00
M 63 x 1,5	43 - 50	70	35	14	EX1126.63.500	118.6350.00



Auf Anfrage:

- in Edelstahl 1.4305 und 1.4435
- NPT Anschlussgewinde

On request:

- in stainless steel 1.4305 and 1.4435
- NPT thread