

EXIOS

116.04

Material: Messing blank
 Dichtungen: Silikon, VMQ
 Klemmeinsatz: PA 6
 Armierung: Metallic Armour or Screen
 Temperaturbereich: -60° C – 105° C
 Dichtigkeit: IP 66, 67 und 68 (5 bar)

Material: brass
 Seals / O-Rings: silicone, VMQ
 Clamping insert: PA 6
 Armour: Metallic Armour or Screen
 Temperature Range: -60° C – 105° C (-76 °F – 221 °F)
 Protection: IP 66, 67 and 68 (5 bar)

Zertifikate: BVS 10 ATEX E 062 X
 IECEx BVS 10.0078X

Certificates: BVS 10 ATEX E 062 X
 IECEx BVS 10.0078X




Weitere internationale Zulassungen vorhanden

Further international approvals available



Gewinde Entry Thread	A1 mm	A2 mm	mm	H max.	GL mm	D mm	Armierung / Armour Klemmring / Clamping Ring		EXIOS	HUGRO No.
							1	2		
M 16 x1,5	6-12	3-8,1	22	69,5	16	27	0-0,7	0,7-1,25	1.605.1600.50	116.1712.04
M 20 x1,5	6-12	3-8,1	22	69,5	16	27	0-0,7	0,7-1,25	1.605.2000.50	116.2012.04
M 20 x1,5	9-16	6-12	24	74,3	16	29	0-0,7	0,7-1,25	1.605.2000.51	116.2016.04
M 20 x1,5	12,5-20,5	9-14	30	80,5	16	35	0-0,7	0,7-1,4	1.605.2000.52	116.2020.04
M 25 x1,5	12,5-20,5	9-14	30	80,5	16	35	0-0,7	0,7-1,4	1.605.2500.51	116.2520.04
M 25 x1,5	16,9-26	12,5-20,5	36	91	16	42	0-0,7	0,9-1,6	1.605.2500.50	116.2526.04
M 32 x1,5	22-33	16,9-26	46	96	16	52	0-0,7	1,3-2,0	1.605.3200.50	116.3233.04
M 40 x1,5	28-41	22-33	55	107	16	64	0-0,7	1,3-2,0	1.605.4000.50	116.4041.04
M 50 x1,5	36-52,6	28,9-44,4	65	131,5	16	73	0-1,0	1,5-2,5	1.605.5000.50	116.5053.04
M 63 x1,5	46-65,3	39,9-56,3	80	144,5	16	90	0-1,0	1,5-2,5	1.605.6300.50	116.6365.04
M 75 x1,5	57-78	50,5-68,2	95	154	16	107	0-1,0	1,5-2,5	1.605.7500.50	116.7478.04
NPT 3/8"	6-12	3-8,1	22	69,5	16	27	0-0,7	0,7-1,25	1.605.3800.70	116.3912.04
NPT 1/2"	9-16	6-12	24	74,3	20	29	0-0,7	0,7-1,25	1.605.1200.70	116.1916.04
NPT 1/2"	12,5-20,5	16,9-26	30	80,5	20	35	0-0,7	0,7-1,4	1.605.1200.71	116.1920.04
NPT 3/4"	16,9-26	12,5-20,5	36	91	20,5	42	0-0,7	0,9-1,6	1.605.3400.70	116.3526.04
NPT 1"	22-33	16,9-26	46	96	25	52	0-0,7	1,3-2,0	1.605.1000.70	116.7533.04
NPT 1 1/4"	28-41	22-33	55	107	26	64	0-0,7	1,3-2,0	1.605.5400.70	116.7641.04
NPT 1 1/2"	28-41	22-33	55	107	26,5	64	0-0,7	1,3-2,0	1.605.6400.70	116.7741.04
NPT 2"	36-52,6	28,9-44,4	65	131,5	27	73	0-1,0	1,5-2,5	1.605.2000.70	116.7853.04
NPT 2 1/2"	46-65,3	39,9-56,3	80	144,5	40	90	0-1,0	1,5-2,5	1.605.5200.70	116.7965.04
NPT 3"	57-78	50,5-68,2	95	154	41,5	107	0-1,0	1,5-2,5	1.605.3000.70	116.8078.04



Auf Anfrage:

- in Messing vernickelt
- in Edelstahl
- mit Zugentlastungsbügel

On request:

- Brass nickel plated
- stainless steel
- with traction relief